

Foret queue réduite DIN338

Reduced shank drill DIN338

Spiralbohrer Abgesetztem Zylinderschaft DIN338

Broca con mango reducido DIN338

Queue / Shank : Ø13



Ø mm	L1 mm	L2 mm
13,5	160	108
14	160	108
14,5	169	114
15	169	114
15,5	178	120
16	178	120
16,5	184	125

Ø mm	L1 mm	L2 mm
17	184	125
17,5	191	130
18	191	130
18,5	198	135
19	198	135
19,5	205	140
20	205	140

Unité de conditionnement : unitaire.

Unit packet : unitary.

Recommandé pour :

Suitable for :

- ◆ Acier / Steel
- ◆ Aluminium
- ◆ Fonte / Cast iron
- ◆ Bois dur / Hard wood

Disponible en coffret :

Available in set :



Queue / Shank : Ø13



Ø mm	L1 mm	L2 mm
13,5	160	108
14	160	108
14,5	169	114
15	169	114
15,5	178	120
16	178	120
16,5	184	125

Ø mm	L1 mm	L2 mm
17	184	125
17,5	191	130
18	191	130
18,5	198	135
19	198	135
19,5	205	140
20	205	140

Unité de conditionnement : unitaire.

Unit packet : unitary.

Recommandé pour :

Suitable for :

- ◆ Acier / Steel
- ◆ Acier dur / Hard steel
- ◆ Aluminium
- ◆ Inox / Stainless steel
- ◆ Fonte / Cast iron
- ◆ Bois / wood
- ◆ Bois dur / Hard wood

Référence / Code

11GBXQ13

DIN 338

Nuance Material	HSS
Type	Meulé Fully ground
Aspect Surface	Gold & Black
Hélice Helix	Normale
Goujure Flute	Normale
Angle pointe Point angle	135°
Affûtage Point shapes	Croix Split point

Référence / Code

11COQ13

DIN 338

Nuance Material	Co5%
Type	Meulé Fully ground
Aspect Surface	Gold
Hélice Helix	Normale
Goujure Flute	Normale
Angle pointe Point angle	135°
Affûtage Point shapes	Croix Split point