

OUTILS BÉTON

CONCRETE TOOLS / KONKRETEWERKZEUGE / HERRAMIENTAS PARA HORMIGÓN

Trépan SDS PLUS

SDS + Hole saw

Bohrkrone SDS +

Corona SDS +

Important : les articles sont vendus séparément

Warning : items are sold separately



**Pour marteaux perforateurs
SDS+ jusqu'à 950W**

Référence / Code

TBD


Nuance
Material

HM/TCT/MD

Recommandé pour :

Suitable for :

- ◆ Béton / Concrete
- ◆ Béton armé / Reinforced concrete
- ◆ Agglo



Ø mm	L1 mm	L2 mm	Ø Filetage Ø Thread
30	70	50	M16
35	70	50	M16
40	70	50	M16
45	70	50	M16
50	70	50	M16
60	70	50	M16
68	70	50	M16
80	70	50	M16
85	70	50	M16
90	70	50	M16
105	70	50	M16
125	70	50	M16
130	70	50	M16

Unité de conditionnement : unitaire.

Unit packet : unitary.

APPLICATION

S'utilise en rotation percussion dans les matériaux durs tels que la brique, le béton ou la pierre. Dans le cas d'une paroi faïencée, traverser la faïence en rotation simple puis en percussion dès que la faïence est traversée.

**Liaison filetée, foret centreur
indépendant serré par vis.**

APPLICATION

Used in rotary percussion for hard materials such as brick, concrete or stone. In the case of a wall with faïence, cross earthenware in simple rotation and percussion as soon as the faïence is crossed.

**Threaded connection, independent
centering drill tightened by screw.**